

4K PRODUCT SPECIFICATIONS

SYSTEM DETAILS

System Capabilities	DVB-S2; MPEG-4 Part10, HEVC
Demodulator Front End	DVB-S2 8PSK and QPSK
Video Decoder	MPEG-4 PART 10; HEVC up to 4K p60
Video Format	PAL

SATELITE SIGNAL INPUT

Impedance	75 Ohm
Frequency Range	950MHz – 2150MHz
LNB Supply	13/18 V, 500 mA
Min. Signal Level	-65dBm to -25dBm

POWER SUPPLY

Input Voltage Range	AC 100 – 270, 50-60 Hz
Power Supply	Adaptor DC 12V / 3.17A, 38 Watts
Power Consumption	38 W

CONNECTIONS

1 Satellite Signal Input	F-Type Female IEC 60169-24
Composite Video Output	IEC 48B Sec 316 (RCA) Female (Yellow)
Composite Audio Output	IEC 48B Sec 316 (RCA) Female (White & Red)
HDMI Video Output	HDMI Receptacle Connector
SPDIF Output	Optical
USB Port	USB Type A Socket [2 No.s]
Ethernet Connection	RJ 45

GENERAL

Dimensions	300 mm (W) x 193 mm (D) x 57.5 mm (H)
Net Weight	.86 Kg
Operating Temperature Range	0-50 deg C
HDMI Cable	HDMI 19P / M Moulding Type; 1500mm
Remote Batteries	CR2025